

<b>APPLICATION CHART OF FRICTION COATING GRIT</b>	
<b>Grit</b>	<b>Rubber and Polyurethane</b>
<b>32 Series</b>	<b>&lt; 50 SHORE A (SOFT)</b>
<b>35 Series</b>	
<b>38 Series</b>	
<b>40 Series</b>	
<b>50 Series</b>	
<b>60 Series</b>	<b>60 - 70 SHORE A (MEDIUM)</b>
<b>70 Series</b>	
<b>80 Series</b>	
<b>90 Series</b>	<b>&gt; 80 SHORE A (HARD)</b>
<b>100 Series</b>	
<b>125 Series</b>	
<b>132 Series</b>	
Consult with our Technical Support Department to discuss the best wheel for your application.	

**FINE**

**COARSE**

<b>FRICITION COATING APPLICATION FORM</b>				
<b>ROLLER INFORMATION</b>				
<b>MATERIAL</b>	<b>RUBBER</b>	<b>POLYURETHANE</b>	<b>OTHER</b>	<b>DUROMETER</b>
PRINTING ROLL	<input type="checkbox"/>	<input type="checkbox"/>		
INDUSTRIAL ROLL	<input type="checkbox"/>	<input type="checkbox"/>		
<b>GRINDER INFORMATION</b>				
<b>GRINDER</b>	<b>MANUFACTURE / BRAND</b>	<b>HORSE POWER</b>	<b>MAX. RPM</b>	<b>VARIABLE SPEED Y/N</b>
TOOLPOST				<input type="checkbox"/> YES <input type="checkbox"/> NO
MEDIUM SPEED				<input type="checkbox"/> YES <input type="checkbox"/> NO
HIGH SPEED				<input type="checkbox"/> YES <input type="checkbox"/> NO